
जापानी तकनीक से बना

ड्युट्रोन कानाफ्लेक्स सक्शन एवं डिलिवरी होज

किसानों और उद्योगों का सच्चा साथी



Key Features

Available Sizes

20 mm to 100 mm I.D.

- · Light in Weight
- Flexibility is retained no cracks or brittleness
- No kinking, bulging or bursting even in the most serious working conditions
- Excellent resistance to high vacuum/pressure

Pressure at 30°C

- Working Pressure 3.5kg/cm² to 7kg/cm²
- Bursting Pressure 11kg/cm² to 24kg/cm²




Medium Duty Suction & Delivery of water for irrigation purpose in agriculture, saline water, light acids, alkalis and other chemicals except solvents.

Product Specifications

Nominal Size		Diameter		Bending	Pressure (at 30°C)		Standard
Inches	mm	ID mm	OD mm	Radius mm	Working kg/cm ²	Bursting kg/cm ²	lengths mtrs.
3/4	20	19.0*	23.6**	45	7.0	24.0	30/50
1	25	25.4*	30.0**	55	7.0	23.0	30/50
11/4	30	31.8*	36.8**	75	6.5	20.0	30/50
11/2	40	38.0*	43.3**	95	5.0	16.0	30/50
2	50	50.8*	57.8***	122	4.0	16.0	30/45/50
21/2	65	63.5*	72.0***	160	4.0	16.0	30/45
3	75	76.2*	85.0***	272	3.5	15.0	30/36
4	100	101.2*	112.2****	290	3.5	11.0	15/18/30

Recommended maximum working temperature: $60/70^{\circ}$ C Variation in ID/OD: [* = ± 0.5] [**= ± 1.0] [***= ± 1.5] [**** =± 2.0]







DUTRON PLASTICS LIMITED

"Dutron House", Nr. Mithakhali Underbridge Navrangpura, Ahmedabad 380 009 Gujarat, India.

Tel: +91 79 2656 1849, 2642 7522

Fax: +91 79 2642 0894
Email: sales@dutronindia.com
Website: www.dutronindia.com

Authorised Dealer