

Spreading Joy Enhancing Lives



Superior to rubber Superior to anyone else

Key Features

- Embedded Spiral Steel Wire reinforcement inside wall of flexible PVC Tubing
- Made from non-toxic compound that provides safe use in the food products
- Lightweight
- High elastic abrasive resistance
- · Kink and crush resistant
- Handles Pressure and full vacuum applications
- Excellent transparency and smooth surface for good visual flow characteristics

Applications

Chemical transfer, vacuum lines, floor cleaning, food and beverage lines, material handling, water feeds; in chemical, pharmaceutical, oil, shipping, sanitary industry

Available Sizes

12 mm to 65 mm I.D.

Product Specifications

Size in mm	I.D. mm	O.D. mm	Wall Thickness in mm	Working Pressure at 30°C kg/cm²	Standard Length mtrs
12	12.7	18.7	3.0 ± 0.2	7	50, 100
15	15.8	22.8	3.5 ± 0.2	6	50, 100
20	19.1	26.1	3.5 ± 0.2	6	30, 50, 100
25	25.4	33.4	4.0 ± 0.2	5	30, 50, 100
30	31.8	39.8	4.0 ± 0.2	5	30, 50, 100
40	38.1	47.1	4.5 ± 0.2	5	30, 50
50	50.8	60.8	5.0 ± 0.2	5	30, 50
65	63	74	5.5 ± 0.2	5	30





DUPLNIPPON POLYMERS PVT. LTD.

"Dutron House", Nr. Mithakhali Underbridge Navrangpura, Ahmedabad 380 009 Gujarat, India.

Tel: +91 79 2656 1849, 2642 7522, 2656 1669

Fax: +91 79 2642 0894 Email: sales@dutronindia.com Website: www.dutronindia.com **Authorised Dealer**

