


Spreading Joy
Enhancing Lives



DUTRON[®] DN 125 CM X 3000 IS: 12818 CM/L-7452575

uPVC CASING PIPES

are manufactured as per IS 12818. These pipes are available in deep blue colour and sizes from 40 mm to 250 mm I.D. Casing Pipes are available in CS type and CM type for shallow and medium Borewells.



○ Key Features

- Ideal for medium and shallow borewells.
- Light weight.
- Non-toxic.
- Excellent corrosion resistance.
- Excellent stiffness.
- Convenient 3 meters length with one side male threaded and other female threaded.
- Conforming to IS 12818.
- Slotted pipes are also available.

○ Applications

As submersible casing pipes for medium (CM - above 80 meters depth) or shallow (CS, up to 80 meters depth) borewells.

○ Available Sizes

40 mm to 250 mm I.D.

○ Product Specifications

Nominal Diameter (DN)		Mean outer Diameter (D) of pipe (mm)		Wall Thickness (mm)			
				Type - CM		Type - CS	
Inches	mm	Min	Max	Min.	Max.	Min.	Max.
1½	40	48.00	48.20	3.50	4.00	—	—
2	50	60.00	60.20	4.00	4.60	—	—
3	80	88.00	88.30	4.00	4.60	—	—
4	100	113.00	113.30	5.00	5.70	4.00	4.40
5	125	140.00	140.40	6.50	7.30	4.90	5.40
6	150	165.00	165.40	7.50	8.50	5.70	6.50
7	175	200.00	200.50	8.80	9.80	7.00	7.80
8	200	225.00	225.50	10.00	11.20	7.60	8.80
10	250	280.00	280.50	12.50	14.00	9.60	11.00

Note:- SDR casing pipe series for shallow depths are also available with company standard in 6 meter length as per SDR 35 & SDR 52.

DUTRON®

DUTRON POLYMERS LIMITED

“Dutron House”, Nr. Mithakhali Underbridge
Navrangpura, Ahmedabad 380 009 Gujarat, India.

Tel : +91 79 2656 1849, 2642 7522

Fax : +91 79 2642 0894

Email : sales@dutronindia.com

Website : www.dutronindia.com

Authorised Dealer